


VISOR® V10 Object Standard, wide field of view

Vision sensor for object detection, simple presence and completeness checks




PRODUCT HIGHLIGHTS

- User-friendly configuration and viewer software with hierarchical user rights
- Detectors for object detection
- Efficient part detection and tracking
- Precise position determination: X/Y-position and orientation
- Comprehensive logic functions for digital switching outputs

Optical data		Functions	
Resolution	800 x 600 pixels	Number of jobs / detectors	32 / 32
Imaging chip CMOS	1/3.6", monochrome / color	Detectors	Position tracking: X/Y and orientation; Pattern matching, contour: teach-in and detection of patterns and contours; Calliper: distance between edges; Grey threshold, brightness: evaluation of brightness; Contrast: evaluation of contrast; Color area²: area inspection of colors, with selectable tolerance
Integrated lens, focal length [mm]	5.2 (wide)		
Pixel size	4.8 µm x 4.8 µm		
Focus	Motorized		
Adjustment range	0 mm to infinity		
Integrated illumination	White (4500 K), red (625 nm) ¹ , infrared (850 nm) ¹ LEDs		
Minimum field of view, X x Y	2 x 1 mm		
Electrical data		Mechanical data	
Operating voltage, +U _B	18 ... 30 DC ³	Dimensions	70.4 x 45 x 45 mm (without plug)
Current consumption (without I/O)	≤ 300 mA	Enclosure rating	IP 67 & IP 65
Protective circuits	Reverse-polarity protection, U _B / short-circuit protection of all outputs	Material, housing	Aluminium, die-cast, RoHS compliant
Power On Delay	Approx. 13 s after Power on	Material, front screen	Plastic
Outputs	PNP/NPN (switchable)	Ambient temperature: operation	0 ... +50 °C ⁴
Max. output current (per output)	50 mA, 100 mA (pin 12)	Ambient temperature: storage	-20 ... +60 °C ⁴
Switching threshold inputs incl. encoder	PNP/NPN High > U _B -1V / Low < 3V	Weight	Approx. 200 g
Input resistance	> 20 kΩ	Plug connections	Supply and I/O M12, 12-pin, Ethernet M12, 4-pin
Interfaces	Ethernet (LAN), EtherNet/IP, PROFINET, SensoWeb	Vibration resistance	EN 60068-2-6
Inputs/outputs	2 inputs, 2 outputs, 4 selectable inputs/outputs	Shock resistance	EN 60068-2-27
Encoder	No		

¹ Not color hardware ² Color hardware ³ Max. ripple < 5 V_{SS} ⁴ 80 % air humidity, noncondensing


VISOR® vision sensor



153-13554

3

Field of view V10, wide



155-03101

----- Increased depth of field
 _____ Normal depth of field

Illumination	Part number	Article number	Accessories
White	V10-OB-S3-W-W-M2	631-91043	Connection cables
Red	V10-OB-S3-R-W-M2	631-91045	Illumination
Infrared	V10-OB-S3-I-W-M2	631-91047	Brackets
White	V10C-OB-S3-W-W-M2	631-91049	Interface accessories
			www.sensopart.com/en/accessories